

4 DSP extension for modular elmeg ICT systems

elmeg Module 4 DSP

- 4 voice channels for media crossing
- Codecs: G.711, G.723, G.726, G.729

elmeg Module 4 DSP

4 DSP extension for modular elmeg ICT systems

Module M 4 DSP provides 4 DSP channels for modular elmeg ICT systems (T444, T484, ICT, hybrid 300 / 600) and ensures the media transfer to IP telephones or to SIP providers.

Product description

To provide optimum voice quality with minimum bandwidths, the standard voice codecs G.711, G.723.1, G.726, and G.729a/b are supported.

In elmeg ICT systems


With the combination of elmeg ICT PBX, VoIP-VPN Gateway, and up to two extension modules M 4 DSP is the ICT system converted to a complete switched network-to-IP gateway. This permits the transition of IP voice data into the traditional voice network and vice versa.

In elmeg T444 / T484

The elmeg T444 / T484 can be directly connected with SIP providers using one M 4 DSP module.

In elmeg hybrid 300 / 600 systems

With respect to media transfer, i.e. the connection from "traditional" technology to IP telephones or to SIP providers, the elmeg hybrid 300 / 600 can be upgraded if required by a further 2 powerful DSP modules (special module slots) that provide parallel usable media transfers.



Variants

M 4 DSP (1092189)

Module with 4 digital, highly compressed voice channels, speech compression (Codecs) as per G.711, G.723.1, G.726, G.729a/b